

ASSIST PLUG MATERIAL— TYPE: HYTAC-B1X


B1X Character	
Color	light blue
Density	672 - 737 kg/m ³
Thermal conductivity	0.19 W/mK
Coefficient of thermal expansion	67.7 x 10 ⁻⁶ m/m/° C
Compressive strength	49.2 Mpa
Service temperature	176° C

HYTAC -- B1X STANDAR SIZE

ROD standard size	Diameter		Length				
	INCH	MM	INCH	MM			
B1X-2 * 24	2	51	24	610			
B1X-2.5 * 24	2.5	64	24	610			
B1X-3 * 24	3	76	24	610			
B1X-3.5 * 24	3.5	89	24	610			
B1X-4 * 24	4	102	24	610			
B1X-4.5 * 24	4.5	114	24	610			
B1X-5 * 24	5	127	24	610			
B1X-5.5*24	5.5	140	24	610			
B1X-6 * 24	6	152	24	610			
B1X-7 * 24	7	178	24	610			
B1X-8 * 24	8	203	24	610			
B1X-9 * 24	9	229	24	610			
B1X-9.5 * 24	9.5	241	24	610			
SHEET standard size	THICNESS		Length		Width		
	INCH	MM	INCH	MM	INCH	MM	
Hytac B1X, 1.0 x 24 x 24	1.0	25.4	24	610	24	610	
Hytac B1X, 1.0 x 24 x 48	1.0	25.4	24	610	48	1219	
Hytac B1X, 1.5 x 24 x 24	1.5	38	24	610	24	610	
Hytac B1X, 1.5 x 24 x 48	1.5	38	24	610	48	1219	
Hytac B1X, 2.0 x 24 x 24	2.0	51	24	610	24	610	
Hytac B1X, 2.0 x 24 x 48	2.0	51	24	610	48	1219	
Hytac B1X, 2.5 x 24 x 24	2.5	64	24	610	24	610	
Hytac B1X, 2.5 x 24 x 48	2.5	64	24	610	48	1219	
Hytac B1X, 3.0 x 24 x 24	3.0	76	24	610	24	610	
Hytac B1X, 3.0 x 24 x 48	3.0	76	24	610	48	1219	
Hytac B1X, 3.5 x 24 x 24	3.5	89	24	610	24	610	
Hytac B1X, 3.5 x 24 x 48	3.5	89	24	610	48	1219	
Hytac B1X, 4.0 x 24 x 24	4.0	102	24	610	24	610	
Hytac B1X, 4.0 x 24 x 48	4.0	102	24	610	48	1219	
Hytac B1X, 4.5 x 24 x 24	4.5	114	24	610	24	610	
Hytac B1X, 4.5 x 24 x 48	4.5	114	24	610	48	1219	
Hytac B1X, 6.0 x 24 x 24	6.0	152	24	610	24	610	